

New Construction Energy Code Compliance Certificate

Per R401.3 Certificate. A building certificate shall be posted on or in the electrical distribution panel.

Date Certificate Posted



Mailing Address of the Dwelling or Dwelling Unit	City
Name of Residential Contractor	MN License Number

THERMAL ENVELOPE										RADON CONTROL SYSTEM		
Insulation Location	Total R-Value of all Types of Insulation	Type: Check All That Apply								Passive (No Fan)		
		Non or Not Applicable	Fiberglass, Blown	Fiberglass, Batts	Foam, Closed Cell	Foam Open Cell	Mineral Fiberboard	Rigid, Extruded Polystyrene	Rigid, Isocyanurate	Active (With fan and monometer or other system monitoring device)		
Below Entire Slab											Location (or future location) of Fan:	
Foundation Wall											Other Please Describe Here	
Perimeter of Slab on Grade												
Rim Joist (1st Floor)												
Rim Joist (2nd Floor+)												
Wall												
Ceiling, flat												
Ceiling, vaulted												
Bay Windows or cantilevered areas												
Floors over unconditioned area												
Describe other insulated areas												

Building envelope air tightness:		Duct system air tightness:	
Windows & Doors		Heating or Cooling Ducts Outside Conditioned Spaces	
Average U-Factor (excludes skylights and one door) U:		Not applicable, all ducts located in conditioned space	
Solar Heat Gain Coefficient (SHGC):		R-value	

MECHANICAL SYSTEMS						Make-up Air <i>Select a Type</i>	
Appliances	Heating System		Domestic Water Heater	Cooling System			
Fuel Type						Not required per mech. code	
Manufacturer						Passive	
Model						Powered	
Rating or Size	Input in BTUS:		Capacity in Gallons:		Output in Tons:		Interlocked with exhaust device. Describe:
Efficiency	AFUE or HSPF%				SEER /EER		Other, describe:
Residential Load Calculati	Heating Loss		Heating Gain		Cooling Load		Location of duct or system:
						Cfm's	
						" round duct OR	
						" metal duct	

MECHANICAL VENTILATION SYSTEM						Combustion Air <i>Select a Type</i>	
Describe any additional or combined heating or cooling systems if installed: (e.g. two furnaces or air source heat pump with gas back-up furnace):						Not required per mech. code	
Select Type						Passive	
Heat Recover Ventilator (HRV) Capacity in cfm's:	Low:		High:		Other, describe:		
Energy Recover Ventilator (ERV) Capacity in cfm's:	Low:		High:		Location of duct or system:		
Balanced Ventilation capacity in cfm's:							
Location of fan(s), describe:						Cfm's	
Capacity continuous ventilation rate in cfm's:						" round duct OR	
Total ventilation (intermittent + continuous) rate in cfm's:						" metal duct	